



Annex to Solar Keymark Certificate Supplementary Information	Licence Number	011-7S605 R
	Issued	2020-08-30

Annual collector output in kWh/collector at mean fluid temperature $\vartheta_m$													
Collector name	Standard Locations $\vartheta_m$	Athens			Davos			Stockholm			Würzburg		
		25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
AS 100 DF6		1'462	1'297	1'111	1'259	1'089	915	903	763	624	971	823	673
Annual output per m <sup>2</sup> gross area		969	859	736	834	722	606	598	506	414	644	545	446
Annual efficiency, $\eta_a$		55%	49%	42%	51%	44%	37%	51%	43%	35%	52%	44%	36%
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m <sup>2</sup>			1630 kWh/m <sup>2</sup>			1166 kWh/m <sup>2</sup>			1244 kWh/m <sup>2</sup>		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		
The collector is operated at constant temperature $\vartheta_m$ (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.1 (September 2019). A detailed description of the calculations is available at <a href="http://www.estif.org/solarkeymarknew/">http://www.estif.org/solarkeymarknew/</a>													

Additional Information					
Collector heat transfer medium	Water-Glycole				
The collector is deemed to be suitable for roof integration	No				
The collector was tested successfully under the following conditions:					
Climate class (A+, A, B or C)				A	--
G (W/m <sup>2</sup> ) >	1000	$\vartheta_a$ (°C) >	20	$H_x$ (MJ/m <sup>2</sup> ) >	600
Maximum tested positive load				2400	Pa
Maximum tested negative load				2400	Pa
Hail resistance using steel ball (maximum drop height)				35	m
Additional collector attribute(s)					
<input type="checkbox"/> Using external power source(s) for normal operation	<input type="checkbox"/> Active or passive measure(s) for self-protection				
<input type="checkbox"/> Co-generating thermal and electrical power	<input checked="" type="checkbox"/> Façade collector(s)				

Energy Labelling Information		Additional Informative Technical Data	
	Reference Area, $A_{sol}$ (m <sup>2</sup> )	Hydraulic Designation Code	Aperture Area, $A_a$ (m <sup>2</sup> )
AS 100 DF6	1.51	6-VH-12S-A:4.8,3950-C:22,700	1.12

Data required for CDR (EU) No 811/2013 - Reference Area $A_{sol}$		Data required for CDR (EU) No 812/2013 - Reference Area $A_{sol}$	
Collector efficiency ( $\eta_{col}$ )	52%	Zero-loss efficiency ( $\eta_0$ )	0.57
Remark: Collector efficiency ( $\eta_{col}$ ) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m <sup>2</sup> , expressed in % and rounded to the nearest integer. Deviating from the regulation $\eta_{col}$ is based on reference area ( $A_{sol}$ ) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.		First-order coefficient ( $a_1$ )	0.91
		Second-order coefficient ( $a_2$ )	0.006
		Incidence angle modifier IAM (50°)	1.03
		Remark: The data given in this section are related to collector reference area ( $A_{sol}$ ) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.	