

AENOR

Keymark Certificate Solar thermal energy



078/000264

AENOR certifies that the organization

BDR THERMEA GROUP B.V

registered office MERCHANTSTRAAT, 55 7300 AA APELDOORN (Holanda - Países Bajos)

supplies Solar collectors

in compliance with UNE-EN 12975-1:2006+A1:2011 (EN 12975-1:2006+A1:2010)

Trade Mark DE DIETRICH DH200 SL
Technical information Specified in Annexes to the Certificate

Production site CL MANGANÉS, 2 08755 CASTELLBISBAL (Barcelona - España)

Certification scheme In order to grant this Certificate, AENOR has tested the product and has verified the quality system implemented for its manufacture. AENOR performs these tasks periodically while the Certificate has not been cancelled, in accordance with Specific Rules RP 078.01.

First issued on 2016-02-16

Last issued on 2021-02-16

Validity date 2026-02-16

Rafael GARCÍA MEIRO
Chief Executive Officer

Original Electronic Certificate

AENOR INTERNACIONAL S.A.U.
Génova, 6. 28004 Madrid. España
Tel. 91 432 60 00.- www.aenor.com

Product certification body accredited by ENAC, number 1/C-PR271



| | | |
|---|----------------|------------|
| Annex to Solar Keymark Certificate Supplementary Information | Licence Number | 078/000264 |
| | Issued | 2021-02-16 |

| Annual collector output in kWh/collector at mean fluid temperature ϑ_m | | | | | | | | | | | | | |
|--|---------------|---|-------|------|-------------------------|-------|------|-------------------------|------|------|-------------------------|------|------|
| Standard Locations | | Athens | | | Davos | | | Stockholm | | | Würzburg | | |
| Collector name | ϑ_m | 25°C | 50°C | 75°C | 25°C | 50°C | 75°C | 25°C | 50°C | 75°C | 25°C | 50°C | 75°C |
| DE DIETRICH DH200 SL | | 2.268 | 1.547 | 928 | 1.678 | 1.088 | 607 | 1.247 | 766 | 415 | 1.363 | 831 | 444 |
| Annual output per m ² gross area | | 1.123 | 766 | 459 | 831 | 539 | 301 | 617 | 379 | 206 | 675 | 412 | 220 |
| Annual efficiency, η_a | | 64% | 43% | 26% | 51% | 33% | 18% | 53% | 33% | 18% | 54% | 33% | 18% |
| Fixed or tracking collector | | Fixed (slope = latitude - 15°; rounded to nearest 5°) | | | | | | | | | | | |
| Annual irradiation on collector plane | | 1765 kWh/m ² | | | 1630 kWh/m ² | | | 1166 kWh/m ² | | | 1244 kWh/m ² | | |
| Mean annual ambient air temperature | | 18,5°C | | | 3,2°C | | | 7,5°C | | | 9,0°C | | |
| Collector orientation or tracking mode | | South, 25° | | | South, 30° | | | South, 45° | | | South, 35° | | |
| The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.1 (September 2019). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/ | | | | | | | | | | | | | |

| Additional Information | | | |
|---|---------------|------------------------------|-----|
| Collector heat transfer medium | Water-Glycole | | |
| The collector is deemed to be suitable for roof integration | No | | |
| The collector was tested successfully under the following conditions: | | | |
| Climate class (A+, A, B or C) | A | | -- |
| G (W/m ²) > | 1000 | ϑ_a (°C) > | 20 |
| | | H_x (MJ/m ²) > | 600 |
| Maximum tested positive load | 2400 | | Pa |
| Maximum tested negative load | 2400 | | Pa |
| Hail resistance using ice balls (diameter) | 25 | | mm |

| Additional collector attribute(s) | | | |
|-----------------------------------|---|--------------------------|--|
| <input type="checkbox"/> | Using external power source(s) for normal operation | <input type="checkbox"/> | Active or passive measure(s) for self-protection |
| <input type="checkbox"/> | Co-generating thermal and electrical power | <input type="checkbox"/> | Façade collector(s) |

| Energy Labelling Information | | Additional Informative Technical Data | |
|------------------------------|---|---------------------------------------|--|
| | Reference Area, A_{sol} (m ²) | Hydraulic Designation Code | Aperture Area, A_a (m ²) |
| DE DIETRICH DH200 SL | 2,02 | 1-V-1234S-A:7.3,1610-C:14.6,1226-D | 1,92 |
| | | | |
| | | | |
| | | | |
| | | | |

| Data required for CDR (EU) No 811/2013 - Reference Area A_{sol} | | Data required for CDR (EU) No 812/2013 - Reference Area A_{sol} | |
|--|-----|---|-------|
| Collector efficiency (η_{col}) | 52% | Zero-loss efficiency (η_0) | 0,69 |
| Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017. | | First-order coefficient (a_1) | 3,66 |
| | | Second-order coefficient (a_2) | 0,016 |
| | | Incidence angle modifier IAM (50°) | 0,94 |
| | | | |
| | | Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs. | |