TÜVRheinland®
DIN CERTCO
Precisely Right.

IGTE

Annex to Solar Keymark Certificate			
		Licence Number	**011-7S1418 F**
		Date issued	**2021-08-09**
		Issued by	**DIN CERTCO**

Licence holder	**Regulus spol. S.r.o**	**Country**	Czech Republic
Brand (optional)		**Web**	www.regulus.eu
Street, Number	Do Koutu 1897/3	**E-mail**	regulus@regulus.cz
Postcode, City	Prague 4, 143 00	**Tel**	+420 241 764 506

Collector Type	Flat plate collector

Collector name	**Gross area (A_G)**	**Gross length**	**Gross width**	**Gross height**	**Power output per collector** Gb = 850 W/m2, Gd = 150 W/m2 & u = 1.3 m/s $\vartheta_m - \vartheta_a$					
					0 K	10 K	30 K	50 K	70 K	118 K
	m²	mm	mm	mm	W	W	W	W	W	W
KPG1 ALC	2.52	2 150	1 170	85	1 866	1 770	1 556	1 316	1 050	305
Power output per m² gross area					741	702	617	522	417	121

Performance parameters test method	Quasi dynamic									
Performance parameters (related to A_G)	η0, b	a1	a2	a3	a4	a5	a6	a7	a8	Kd
Units	-	W/(m²K)	W/(m²K²)	J/(m³K)	-	J/(m²K)	s/m	W/(m²K⁴)	W/(m²K⁴)	-
Test results	0.744	3.72	0.013	0.000	0.00	10 360	0.000	0.00	0.0	0.97

Incidence angle modifier test method		Quasi dynamic - outdoor								
Incidence angle modifier	Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°
Transversal	$K_{\theta T,coll}$	1.00	1.00	1.00	0.99	0.96	0.90	0.73	0.37	0.00
Longitudinal	$K_{\theta L,coll}$	1.00	1.00	1.00	0.99	0.96	0.90	0.73	0.37	0.00

Heat transfer medium for testing		Water	
Flow rate for testing (per gross area, A_G)	dm/dt	0.020	kg/(sm²)
Maximum temperature difference during thermal performance test	$(\vartheta_m-\vartheta_a)_{max}$	88	K
Standard stagnation temperature (G = 1000 W/m²; ϑ_a = 30 °C)	ϑ_{stg}	200	°C
Maximum operating temperature	$\vartheta_{max\ op}$	-	°C
Maximum operating pressure	$p_{max,op}$	1000	kPa

Testing laboratory	Institut für Gebäudeenergetik, Thermotechnik und Energiespeicherung (IGTE)	http://www.igte.uni-stuttgart.de	
Test report(s)	20COL1538/1OEM03		09.08.2021
	20COL1538Q/1OEM03		09.08.2021

Comments of testing laboratory — Datasheet version: 6.1, 2019-09-26

Thermal performance parameters are given from test report 20COL1538/1 OEM03 (KPG1 ALC)

TZS Forschungs- und Testzentrum für Solaranlagen
Institut für Thermodynamik und Wärmetechnik
Universität Stuttgart
Pfaffenwaldring 8, 70550 Stuttgart (Vaihingen)

-

Annex to Solar Keymark Certificate	Licence Number	011-7S1418 F
Supplementary Information	Issued	2021-08-09

Annual collector output in kWh/collector at mean fluid temperature ϑ_m

Standard Locations		Athens			Davos			Stockholm			Würzburg		
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
KPG1 ALC		3 053	2 147	1 371	2 300	1 561	951	1 693	1 086	637	1 851	1 180	682
Annual output per m² gross area		1 211	852	544	913	619	378	672	431	253	734	468	271
Annual efficiency, η_a		69%	48%	31%	56%	38%	23%	58%	37%	22%	59%	38%	22%
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m²			1630 kWh/m²			1166 kWh/m²			1244 kWh/m²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		

The collector is operated at constant temperature ϑm (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.1 (September 2019). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/

Additional Information

Collector heat transfer medium				Water-Glycole	
The collector is deemed to be suitable for roof integration				Yes	
The collector was tested successfully under the following conditions:					
Climate class (A+, A, B or C)				A	--
G (W/m²) >	1000	ϑ_a (°C) >	20	H_x (MJ/m²) >	600
Maximum tested positive load				3000	Pa
Maximum tested negative load				2500	Pa
Hail resistance using steel ball (maximum drop height)				2	m

Additional collector attribute(s)

☐ Using external power source(s) for normal operation ☐ Active or passive measure(s) for self-protection

☐ Co-generating thermal and electrical power ☐ Façade collector(s)

Energy Labelling Information

	Reference Area, A_{sol} (m²)
KPG1 ALC	2.52

Additional Informative Technical Data

Hydraulic Designation Code	Aperature Area, A_a (m²)
12-V-1234S-7.2,1988-20.4,1215-D	2.31

Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}

Collector efficiency (η_{col})	57%

Remark: Collector efficiency (ηcol) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m², expressed in % and rounded to the nearest integer. Deviating from the regulation ηcol is based on reference area (Asol) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.

Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}

Zero-loss efficiency (η_0)	0.74	--
First-order coefficient (a_1)	3.72	W/(m²K)
Second-order coefficient (a_2)	0.013	W/(m²K²)
Incidence angle modifier IAM (50°)	0.98	--

Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.

DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin, Germany

Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de